



BladeCote™

Blade & Bit Lubricant

Extends blade & bit life

Will not build-up even after several applications

Will not stain or effect finishing of wood

Contains no petroleum oils or silicone

Description

Regular use of BladeCote™ on saw blades, router and drill bits and knives significantly reduces cutting friction and the buildup of resin or pitch. BladeCote dries in seconds and will not gum-up, even after several applications.

Product Benefits

- Prevents resin buildup. Reduces blade cleanings.
- Extends overall life of blades and bits
- Contains NO silicone or petroleum oil.
- Will NOT stain wood or interfere with glues or finishes.
- Reduces cutting friction and heat.
- Prolongs equipment life by reducing saw or drill motor drag.
- Increases productivity by less downtime for saw blade changeovers.
- Works equally well on steel or carbide, stellite and diamond-tipped cutting blades.

Other Applications

- Chisels
- Shaper Cutters
- Router Bits
- Planer Blades
- Superb, long lasting, penetrating lubricant for numerous industrial, commercial and household uses.

Directions

Shake well before use.

To Prevent Clogging: After each use invert the container and spray until nozzle clears.

To Reduce Friction and Pitch Build-up:

Clean blade or bit with degreasing agent. Spray a thin even coat of BladeCote over entire blade or bit, including gullets and cutting edge. Allow a few seconds to dry.

For Best Results: After several cuts, re-spray BladeCote over entire bit or blade. Re-apply daily or more frequently based upon workload and material being cut.

For Tools: Spray a thin even coat over entire tool surface. Let dry. Buff to shine if desired. Re-apply as needed.



34 Drayton Industrial Dr., Drayton, ON N0G 1P0

Distributed by:

Craftsmen Hardwoods Inc.

TF: 1.800.378.3782

Fax: 519.638.3105

sales@craftsmenhardwoods.com

DANGER! Extremely flammable. Vapor may cause flash fire. Harmful if swallowed. Inhaling vapors harmful. Skin and eye irritant. Contents under pressure. PRECAUTIONS: Because vapors may ignite explosively, prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Keep away from heat, sparks and flame. Do not smoke, extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until vapors are gone. Avoid prolonged or repeated breathing of vapors. Do not misuse by deliberately concentrating and inhaling the contents. Keep container closed when not applying. Wear gloves and eye goggles; avoid contact with skin and eyes. Store in a cool, dry, well-ventilated area away from sunlight. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. FIRST AID: If inhaled, move person to non-contaminated air and give artificial respiration if person is not breathing. Call physician immediately if swallowed; do not induce vomiting. If contacted in eyes, flush with water for at least 15 minutes and seek medical attention. For skin contact, wash immediately with soap and water.

The Limited Warranty for this product can be obtained at www.bostik-us.com/resource-center/warranties or by calling 1-800-726-7845 (choose option 2, then option 2 again). TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES. UNLESS OTHERWISE STATED IN THE LIMITED WARRANTY, THE SOLE REMEDY FOR BREACH OF WARRANTY IS REPLACEMENT OF THE PRODUCT OR REFUND OF THE BUYER'S PURCHASE PRICE. It is the buyer's obligation to test the suitability of the product for an intended use prior to using it. Any claim for a defective product must be led within 30 days of discovery of a problem, and must be submitted with written proof of purchase.

Bostik, Inc.

11320 Watertown Plank Road
Wauwatosa, WI 53226
414-774-2250
1-800-726-7845
www.bostik-us.com
www.bostikdiy.com

This document supercedes all previously published literature.

Y12- 02-17-2012